

**MATERIAL SAFETY DATA SHEET**

PSM High Pressure Laminates

**STATEMENT OF HAZARDOUS NATURE:** In its intact state, this product is classified as not hazardous according to the criteria of Worksafe Australia. Dust from the product is hazardous according to the criteria of Worksafe Australia.

**IMPORTANT NOTICE:** This Material Safety Date Sheet (MSDS) is issued by PSM Railite, S.A., in accordance with Worksafe Australia guidelines. As such, the information contained herein must not be altered, deleted or added to. PSM Railite, S.A. will issue a new MSDS when there is a change in product specifications and/or Worksafe Australia guidelines/regulations. PSM Railite, S.A. will not accept any responsibility for any changes made to its MSDS in content by any other person or organisation.

Product name: PSM High Pressure Laminates

Manufacturer's Product Code: Not applicable

UN number: None Allocated

Dangerous goods class & Subsidiary Risk: None Allocated

Hazchem code: None Allocated

Poisons schedule number: None Scheduled

Use: Decorative surfacing of furniture, cabinets, bench tops, walls, ceiling and doors.

**Physical Description/Properties:**

Appearance: The products are manufactured as high pressure laminates, in sheet form and ranging in thickness from 0,6mm to 20mm. They are made from layers of resin impregnated paper which are bonded together under heat and pressure.

Boiling Point: (°C) Not determined

Melting Point: (°C) Not determined

Vapour pressure: Not determined

Flammability Limits: Not Applicable

Solubility in water: Negligible

Odour Threshold: Newly manufactured and freshly cut surfaces may have a faint resin odour.

Early Fire Hazard Indices to AS 1530.3

Ignitability index: 13

Spread of flame index: 0

Heat evolved index: 2

Smoke developed index: 3

# high pressure laminates

## Ingredients:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportions</u>
Kraft paper	None	50 – 65 %
Decor paper	None	10 – 15 %
Phenol formaldehyde resin	9003 - 35 - A	10 – 15 %
Melamine formaldehyde resin	9003 - 08 - 1	25 – 35 %

Note: The above ingredients are bound together under heat and pressure. The process 'cures' the resin, which bonds with the other substances.

## HEALTH HAZARD INFORMATION

Note: In its intact state this product is not classified as a hazardous substance by Worksafe Australia. Exposures to dust produced from machining the laminates or gas and vapour from heat processing may result in the following health effects.

### Health Effects:

#### Acute:

**Swallowed:** Unlikely to occur but swallowing the dust may result in abdominal discomfort.

**Eye:** The dust, gas and vapour may be irritating to the eyes causing discomfort and redness.

**Skin:** The dust, gas and vapour may irritate the skin, resulting in itching and occasionally a red rash. During handling sharp edges may cut the skin.

**Inhaled:** The dust, gas and vapour may irritate the nose, throat and lungs, especially in people with upper respiratory tract or chest complaints such as asthma.

**Chronic:** Repeated exposures over many years to uncontrolled dust, gas and vapour from these laminates may increase the risk of irreversible health effects including allergic dermatitis, asthma, chronic nose or throat irritation or lung scarring in some people. Formaldehyde has been evaluated by the International Agency for Research on Cancer (IARC) as group 2A, probably carcinogenic to humans.

#### First Aid:

**Swallowed:** Give water to drink. If abdominal discomfort occurs seek medical attention.

**Eye:** Flush with flowing water at least 15 minutes, and if symptoms persist seek medical attention.

**Skin:** Wash with mild soap running water. Seek medical attention if symptoms persist. For cuts, clean wound and apply antiseptic dressing.

**Inhaled:** Leave the dusty area.

**Advice to Doctor:** Treat symptomatically.

**PRECAUTIONS FOR USE****Exposure Standards:**

The Worksafe Australia Exposure Standards, published in May 1995 for formaldehyde and cellulose are:

Cellulose (paper fibre): 10 mg/cubic metre-weighted average (TWA)

Formaldehyde: 1.0 ppm (1.2 mg/cubic metre) time-weighted average (TWA)  
2.0 ppm (2.5 mg/cubic metre) short term exposure limit (STEL)  
Sen – sensitiser: Category 2 carcinogen (probably human carcinogen)

Keep exposures as low as practicable with the aim of maintaining respirable dust levels below 1.0 mg/cubic metre (TWA)

**Engineering Controls:**

All work with these laminates should be carried out in such a way as to minimise the generation of, and exposure to dust. Under factory conditions, sawing, drilling, sanding heat processing etc. should be done with equipment fitted with exhaust devices capable of removing dust, gas and vapour at source. Hand power tools should be fitted with dust bags and used in well ventilated areas.

Work areas should be well ventilated. They should be cleaned at least daily, and dust removed by vacuum cleaning or wet sweeping method.

**Personal Protection:****Skin Protection:**

Wear loose, comfortable clothing. Long-sleeved shirts and trousers are recommended to prevent skin irritation. After handling laminates, wash with mild soap and water. Do not scratch or rub the skin if it becomes irritated. Wash work clothes regularly and separately from other clothes. Comfortable light weight leather or equivalent work gloves (AS 2161) should be worn.

**Eye Protection:**

Dust resistant safety glasses or non fogging goggles (AS/NZS 1336) should be worn when machining.

**Respiratory Protection:**

A class P1 or P2 replaceable filter or disposable half face-piece particulates respirator should be worn when machining. Respirators should comply with AS/NZS 1716 and be selected, used and maintained in accordance with AS/NZS 1715.

**Flammability:**

These laminates are flammable but difficult to ignite. Fine airborne dust can ignite so avoid a build-up of dust and keep all storage and work areas well ventilated. Avoid sources of radiant heat and flame; and avoid sparks and sources of ignition in all electrical equipment, including dust extraction equipment. People must not smoke in storage or work areas.

**SAFE HANDLING INFORMATION****Storage and Transport:**

The laminates should be stored in well ventilated areas away from sources of heat, flame or sparks. No special transport requirements are considered necessary.

**Spills and disposal:**

Off-cuts and general waste material should be placed in containers and disposed of at approved landfill sites, or burnt in an approved furnace or incinerator, in accordance with disposal authority guidelines. Dust from the laminates should be cleaned up by vacuuming or wet sweeping.

**Fire/explosion hazard:**

Burning or smouldering laminates or dust can generate carbon dioxide and other pyrolysis products typical of burning organic material. Use water or dry foam fire extinguishers and avoid breathing smoke from burning or smouldering material. Dry dusts in high concentrations can be explosive.

**Smoking and Other Dust:**

Inhalation of airborne particles from other sources in the work environment, including those from cigarette smoke, may increase the risk of contracting the lung disease associated with exposure to dust from this product. PSM Railite, S.A. recommend that all work and storage areas be smoke free zones and other airborne contaminants be kept to a minimum.

**CONTACT POINT**

For further information on this product, please contact the following:

HALIFAX VOGEL GROUP (ABN 75 104 808 853)  
29 Henderson Street  
Turrella NSW 2205  
Australia  
Tel. + 61(0)2 9556 6000  
Fax. +61(0)2 9556 6066

Whilst the information contained in this document is based on data, which, to the best of our knowledge, was accurate and reliable at the time of preparation, we can accept no responsibility for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, we can accept no responsibility for any loss or damage caused by any person acting or refraining from action as a result of this information.