

VIEWNIQUE™ Surfaces

digital artisan canvas



VIEWNIQUE Surfaces: digital artisan canvas

Type II Physical Properties:

Finished Width:	56"
Finished Total Weight:	20.0 oz./lin. yd.
Finished Total Weight:	13.3 oz./sq. yd.
Backing:	Osnaburg
Average Total Thickness:	.021"
Tensile Breaking Strength:	96 x 92 lbs.
Tear Strength (Scale Reading):	51 x 50
Avg. Adhesion Vinyl to Fabric:	3.0 lbs/inch

Specifications:

Digital Artisan Canvas is a Class A vinyl coated fabric wallcovering manufactured by OMNOVA Solutions Inc., and meets or exceeds G.S.A. Federal Specifications CCC-W-408A, B, C, and D for Type II material and the Canadian General Standard Board 41-GP-30M. Digital Artisan Canvas has been accepted for use by the City of New York Department of Buildings.

Fire Classification:

Digital Artisan Canvas is a Class "A" wallcovering by meeting the following classifications and specifications when tested by ASTM E-84-00:

- NFPA 101-94 Classification
- CCC-W-408A, B, C, and D
- CFFA-W-101-D



Supplied by: Halifax Vogel Group in Australia and New Zealand

Customer Service P: 1300 558 882 (Australia Wide) +61 (02) 9556 6000 (outside Australia)
SYDNEY (Head Office) * MELBOURNE * BRISBANE * PERTH * ADELAIDE * AUCKLAND



Product Features:

viewnique wall surfaces are manufactured Cadmium, Mercury and PFOA Free. They do not contain, nor will they degrade to, Perfluoro Octanoic Acid (PFOA).

viewnique products are provided with a 5-year limited warranty subject to certain conditions and limitations.

For complete warranty terms, go to:

www.omnova.com/dbp_site/viewnique.htm

Permeability, Moisture and Mold:

Vinyl wallcovering has little or no moisture permeability. If the design, construction or maintenance of a building, and/or other circumstances allow moisture to accumulate in a wall or wall cavity, vinyl wallcovering can act as a vapor barrier restricting the escape of moisture and increasing the risk of mold growth. Vinyl wallcovering permeability can be increased through alternative product constructions and perforation with varying results depending on the method used, but it is important to keep in mind that no wall surfacing material, including perforated wallcovering or paint, will prevent mold growth if moisture accumulation and moisture sources are not eliminated. An experienced professional who is familiar with building conditions and circumstances should be consulted concerning required permeability and the benefits and limitations of vinyl wallcovering. For more information on wallcovering permeability and mold, OMNOVA recommends that you visit:

www.omnova.com/dbp_site/permeability.htm

www.wallcoverings.org

viewnique wall surfaces contain additives to resist mold and other micro-biological growth on the product. These additives, however, will not prevent mold growth if moisture is allowed to accumulate in or behind the wall.



The OMNOVA Solutions Inc., Columbus, MS manufacturing facility employs an ISO Quality System and is 9001 Certified.